

CLAIMS

What is claimed is:

1. A method of forming an executable program from a plurality of object code modules, each object code module comprising section data and an ordered sequence of relaxation instructions including a first type defining relocation operations and a second type controlling linker operations, each relaxation instruction having associated therewith a unique instruction count of a sequence of instruction counts, wherein the second type includes a jump relaxation instruction which specifies the instruction count of a relaxation instruction to be subsequently read, the method comprising:

(a) reading each relaxation instruction in the ordered sequence defined by the sequence of instruction counts; and

(b) where said relaxation instruction is of the first type defining a relocation operation, executing that relocation operation on section data to which it relates, and

where said relaxation instruction is a jump relaxation instruction, the next relaxation instruction which is read is that of the instruction count specified in the jump relaxation instruction.

2. A method according to claim 1 wherein said method further comprises recording a pass value indicative of the number of times said ordered sequence of relaxation instructions has been repeated.

3. A method according to claim 2 wherein said method further comprises detecting when a result of a relocation operation executed on said section data has changed between repetitions of said ordered sequence of relaxation instructions and recording a change value indicative of the occurrence of said change.

wherein, when said relaxation instruction defines a relocation operation, the relaxation module executes said relocation operation on section data defined in one or more previous relaxation instructions and, when said relaxation instruction identifies section data, said section data is copied to said executable program, said section data being relocatable by subsequent previous relocation operations.

11. A linker according to claim 10, which comprises state flag means for holding a pass value indicative of the number of times the ordered sequence of said relaxation instructions has been repeated.

12. A method according to claim 11 wherein said linker comprises state flag means for recording a change value indicative of the fact that copied section data has changed between repetitions of execution of the same relaxation instruction of the first type.

13. A linker according to claim 10, wherein the relaxation module comprises means for deriving an offset and a number of bytes of section data to be copied to said executable program from said second type of relaxation instruction.

14. A linker according to claim 10 wherein the relaxation module comprises means for defining a byte of section data to be copied to said executable program.

15. A linker according to claim 10 wherein the linker comprises a stack capable of holding values generated by execution of the relaxation instructions.

16. A linker according to claim 15 wherein a value of a top of the stack is readable by the relaxation module to determine a condition.

where said relaxation instruction is a jump relaxation instruction, the next relaxation instruction which is read is that of an instruction count specified in the jump relaxation instruction

and where the relaxation instruction is a conditional relaxation instruction, accessing a state variable which denotes linker state to determine whether the condition is satisfied.

20. A method according to claim 19 wherein the state variable is a pass value indicative of the number of times said ordered sequence of said relaxation instructions have been repeated.

21. A method according to claim 19 wherein the state variable is a change flag denoting whether a symbol has changed value during repeated executions of the ordered sequence of relaxation instructions.

22. A method of forming an executable program from a plurality of object code modules, each object code module comprising an ordered sequence of relaxation instructions including a first type defining section data, a second type defining relocation operations and a third type controlling linker operations, each relaxation instruction having associated therewith a unique instruction count of a sequence of instruction counts, the method comprising:

reading each relaxation instruction in the ordered sequence defined by the sequence of instruction counts;

where said relaxation instruction defines a relocation operation, executing said relocation operation on section data defined in one or more previously read relaxation instructions;

where said relaxation instruction defines section data, copying said section data to said executable program, said section data being relocatable by subsequent previous relocation operations.